

SECTION 1: COMPANY AND PRODUCT INFORMATION

1.1 GHS Product Identifier

Commercial Product Name: Dura Color Hardener

Chemical Name: Mixture of silica sand, portland cement, pigments and additives (or admixtures)

1.2 Relevant identified uses of product:

Product is a dry-shake color hardener for application on freshly-placed concrete to color and harden the concrete surface. This product is intended for use only by professionals. KEEP OUT OF REACH OF CHILDREN.

1.3 Details of the supplier of the safety data sheet:

DURACORP
2664 Vista Pacific
Oceanside, CA 92056
Phone: (800) 795-4750

1.4 Transportation Emergency Telephone Number: CHEMTREC (800) 424-9300

SECTION 2: HAZARD IDENTIFICATION

2.1 Classification of substance or mixture:

Human Health:

Product contains silica sand, a form of crystalline silica. Properly fitted dust-type respirators can control silica exposure.

Product contains portland cement which when wet can irritate the skin and seriously damage the eyes.

Product may contain titanium dioxide, which is considered to be a class 2B carcinogen by IARC.

Acute toxicity, eyes, SE, H318, category 1

Acute toxicity, dermal, SE, H315, category 2

Carcinogenicity, STOT, lungs, Inhalation, RE, H350, category 1B

GHS Category Key
1 = most hazardous
5 = least hazardous

Environment: Product is not dangerous to the environment, upon water addition it will set to a hard mass that is not biodegradable.

2.2 Label elements:

GHS Hazard (H) Statements:

Acute Toxicity

H315--Causes skin irritation

H318--Causes serious eye damage

Chronic Toxicity

H350--May cause cancer (silicosis) repeated exposure to respirable silica. IARC lists Titanium Dioxide as a 2B carcinogen.

GHS Precautionary (P) Statements:

Prevention Precautionary Statements

P102--Keep out of reach of children

P202--Do not handle until all safety precautions have been read and understood

P280--Wear protective gloves/eye protection/face protection

P284--In case of inadequate ventilation, wear respiratory protection

Response Precautionary Statements

P301+P330+P331--**IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.

P302+P352--**IF ON SKIN:** Wash with plenty of water



GHS Signal Word: **WARNING**

P304+P340--**IF INHALED**: Move person to fresh air and keep comfortable for breathing
 P305+P351+P338--**IF IN EYES**: Rinse cautiously with water for several minutes. Remove contacts and continue rinsing.
 P337+P313--If eye irritation persists, get medical attention

Disposal

P501--Dispose of contents/container in accordance with applicable local/state/federal regulations

2.3 Other hazards:

No other hazards are known.

Refer to Section 16 for wording of terms

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Main Constituent: Crystalline Quartz Silica Sand

3.2 Mixture:

Components of Mixture	CAS #	EINECS #	Weight %
Silica Sand, Crystalline Quartz	14808-60-7	238-878-4	40 -70%
Portland Cement	65997-15-1	266-043-4	30 - 60%
Flyash, Coal Combustion Residuals	68131-74-8	931-322-8	0 - 10%
Respirable Fraction of Silica Dust	14808-60-7	238-878-4	< 0.1%
Various pigments, mixed metal oxides	Mixtures	Mixtures	0 - 10%
Crystalline Quartz, respirable fraction	14808-60-7	238-878-4	<0.1%

The exact percentages and components in this composition have been withheld as trade secrets.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Eye Contact : Quickly flush with plenty of clean water for 15 minutes. Remove contact lenses if easy to do. Open eyelids widely during flushing. If irritation persists, continue flushing during transport to emergency room and bring these instructions for doctor. Provide easy access to eye wash station in work area.
 Inhalation: Move person to fresh air, make comfortable for breathing. Get medical attention if condition worsens.
 Skin Contact: May result in skin irritation. Remove contaminated clothing. Wash skin with soap and water.
 Ingestion: If swallowed, do NOT induce vomiting. Call a POISON CENTER (800) 222-1222 or 911 for instructions on first aid treatment. Transport person to emergency room and bring these safety instructions (SDS).

4.2 Most important symptoms and effects both acute and delayed:

Eye contact with cement (wet or dry) can cause serious and potentially irreversible injuries to eyes. If irritation persists after rinsing eyes, take person to emergency room for treatment.
 Repeated inhalation of respirable silica over long periods of time increases the risk of developing lung disease (silicosis).
 Cement may have an irritating effect that is most severe when sweating. Prolonged skin contact with wet product may cause serious burns that develop without pain being felt.

4.3 Indication of any immediate medical attention and special treatment needed:

Primary routes of entry include: Inhalation (dust), Eye Contact, Skin Contact. Eye contact requires immediate first aid. Refer to SECTION 11 for more detailed information on health effects and symptoms.

SECTION 5: FIRE FIGHTING MEASURES

5.1 Extinguishing media: Use fire extinguishing media appropriate for surrounding fire.

5.2 Special Hazards arising from the substance or mixture:

Fire Hazard: Not flammable
 Explosion Hazard: No explosion hazard

Reactivity: Hazardous reactions will not occur.

5.3 Advice for fire-fighting:

Use normal fire fighting protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions :

General measures: Use personal protective equipment. Provide adequate ventilation. See section 8 for additional information.

Protective equipment: Wear suitable protective clothing with eye protection and gloves.

6.2 Environmental precautions:

Avoid discharge into waterways, sewers and soil. If spill enters water, contact local authorities.

6.3 Methods and material containment and cleaning up:

Method of cleaning up: Collect material in dry state if possible. Avoid generating dust. Recover product by vacuuming, shoveling or sweeping. Use a HEPA type filter on vacuum exhaust to prevent release of particulates into air.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

Do not breathe dust. Avoid creating or spreading dust. Handle in accordance with good industrial hygiene procedures. Always wash hands immediately after handling product. Do not eat or drink in area where product is being used. Repeated exposure to respirable silica over long time periods may cause cancer (silicosis).

7.2 Conditions for safe storage including any incompatibilities:

Store in a covered dry shaded area. Avoid all contact with water.

7.3 Specific end uses: Engineering measures: Use with adequate ventilation in work area. Keep worker exposure of air

This product is intended for use only by professionals to color and harden freshly-placed (new) concrete surfaces.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

NDA = No Data Available


Components of Mixture	ACGIH TLV	OSHA 8-Hour PEL TWA	OSHA PEL 8 hr	NIOSH TWA
Portland Cement	1 mg/m ³	15 mg/m ³	NDA	10 mg/m ³ total
Silica Sand, Crystalline Quartz	0.025 mg/m ³	(10mg/m ³) ÷ (SiO ₂ % + 2)	NDA	0.05 mg/m ³
Crystalline Quartz, Respirable Fraction	0.025 mg/m ³	50 µg/m ³	NDA	5 mg/m ³
Flyash, Coal Combustion Residues	NDA	NDA	NDA	NDA
Misc. iron/chromium oxide pigments, PNOR	3 mg/m ³	15 mg/m ³ total, 5 mg/m ³ dust	NDA	NDA
Titanium Dioxide pigment	10 mg/m ³	5 mg/m ³ as respirable dust	15 mg/m ³ total	NDA
Total Silica Dust	NDA	0.3 mg/m ³	NDA	10 mg/m ³

8.2 Exposure controls:

Avoid breathing dust. Corrosive: Do not get into eyes or on skin.
 Engineering measures: Use only with adequate ventilation. Keep worker exposure of dust and airborne particulates below PEL & TLV limits in section 8.1

8.3 Individual protective measures:

Eye/face protection: Wear tight fitting goggles or safety glasses with side shields to protect eyes.
 Skin protection: Wear protective clothing, rubber apron or coat and neoprene rubber gloves to protect skin.
 Respiratory Protection: In case of inadequate ventilation, or where exposure levels are over limits in section 8.1, wear a proper NIOSH approved particulate-type respirator, such as N95 or P100 filters.
 Hygiene measures: Wash hands after exposure, Remove contaminated clothing, shower and wash with plenty of soap and water. Wash contaminated clothing prior to reuse.
 Environmental exposure controls: Have eye wash stations and emergency showers located near work area.



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information of basic physical and chemical properties

Property-Test	Value/Result
a) pH	10-12 when wet, not applicable when dry
b) Color	various
c) Odor	not applicable
d) Freezing/Melting Point	not applicable
e) Boiling Range	not applicable
f) Flash Point	not applicable
g) Auto ignition Temperature	not applicable
h) Explosive Limits UEL	not applicable
i) Explosive Limits LEL	not applicable
j) Flammability (solid, gas)	not applicable
k) Vapor Pressure	not applicable
l) Vapor density vs air = 1.0	not applicable
m) Density	not applicable
n) Solubility in water	very low (only admixture portion is soluble)
o) KOW Partition Coefficient	not applicable
p) Evaporation Rate	not applicable
q) Specific Gravity, water = 1	2.5 to 3.5
r) VOC	0.0 g/mL (0.0 lb/gal)

9.2 Other information

Other data: Specific Gravity, water = 1.0 3.0 to 5.0

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity:** When water is added, hardening occurs to make a solid mass.
- 10.2 Chemical stability:** Product reacts rapidly with strong acids causing heat evolution
- 10.3 Possibility of hazardous reactions:** Hazardous reactions do not normally occur.
- 10.4 Conditions to avoid:** Avoid contact with strong acids and moisture.
- 10.5 Incompatible materials:** Water causes setting. Strong acids can react with product.
- 10.6 Hazardous decomposition products:** No hazardous decomposition products are known.

SECTION 11: TOXICOLOGICAL INFORMATION

Components of Mixture	LD ₅₀ oral (rat)	LC ₅₀ Inhalation	LD ₅₀ dermal (rabbit)
Portland Cement	2000 mg/kg	NDA	NDA
Silica Sand, Crystalline Quartz	>2,500 mg/kg	NDA	NDA
Sand, Crystalline Quartz, Respirable Fraction	NDA	NDA	NDA
Flyash, Coal Combustion Residuals	>2,000 mg/kg	2.2 mg/L 1 hr	>2,000 mg/kg (skin)
Titanium Dioxide	12,000 mg/kg	>6.82 mg/L rat	10,000 mg/kg
Misc. iron/chromium oxide pigments, PNOR	NDA	NDA	NDA

Toxicity:

- a) acute toxicity, Not classified as an acutely toxic material.
- b) skin corrosion/irritation, Wet cementitious products can cause serious skin irritation.
- c) serious eye damage/irritation, Wet cementitious products can cause serious eye damage.
- d) respiratory or skin sensitization, Repeated exposure to respirable silica can cause serious delayed lung injury.
Portland cement can cause skin sensitization due to Chrome VI presence.

This product is not covered by international regulation of the transport of dangerous goods (IMDG, IATA, ADR, RID)

DOT: Not regulated

14.1 UN Number: Not regulated

14.2 UN proper shipping name: Not classified as dangerous goods under DOT and UN regulations.

14.3 Transport hazard class(es): Not regulated

14.4 Packing group: Not regulated.

Packaging group: Not regulated

14.5 Environmental hazards

Marine pollutant: Not regulated.

Environmentally hazardous substance: Not applicable.

14.6 Special precautions for user: None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and IBC Code: Not regulated.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for substance or mixture.

OSHA Hazcom 2012, 29 CFR 1910.1200 and regulation (EC) No 1272/2008 (CLP) of the European Parliament

15.2 Chemical Safety Assessment: Not required.

For information on labeling go to section 2

There are no TSCA 12b chemicals in this product

SECTION 16: OTHER INFORMATION

Before using, read the Tech-Data for this product, the complete package label and this SDS and Warranty

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Wording of terms:

- ACGIH American Conference of Government Industrial Hygienists.
- CAS No. Chemical Abstract Service, unique chemical identifier
- CERCLA Comprehensive Environmental Response, Compensation and Liability Act
- EC₅₀ Effective Concentration that causes 50% mortality of population
- EINECS European Inventory of Existing Commercial Chemical Substances (EU)
- GHS Global Harmonization System, worldwide chemical safety program
- LC₅₀ Lethal Concentration that causes 50% mortality of population
- LD₅₀ Lethal Dose that causes 50% mortality of population
- NFPA National Toxicology Program
- NTP National Toxicology Program
- OSHA Occupational Safety & Health Administration
- PBT Persistent, Bioaccumulative and Toxic
- PEL Permissible Exposure Limits
- RCRA Resource Conservation and Recovery Act
- RE Repeated Exposure
- RQ Reportable quantity
- SARA III Superfund Amendments and Reauthorization Act
- SDS Safety Data Sheet (GHS replacement for MSDS)
- SE Single Exposure
- STO Specific Target Organ Toxicity
- TLV Threshold Limit Value
- TSCA Toxic Substances Control Act

WHMIS Category:D2B,D2A

WHMIS Signal Word: **WARNING**

Hazardous Material Identification	
Health Hazard	2
Fire Hazard	0
Reactivity Hazard	0
Personal Protection	See Sec. 8 PPE

0 = minimal hazard, 4 = extreme hazard

NFPA 704 Fire

Health 2 0 0 Reactivity

0= low hazard, 4= high hazard

TWA Time Weighted Average
vPvB Very persistent and very bioaccumulative
WHMIS Workplace Hazardous Materials Information System (Canada)

CALIFORNIA PROPOSITION 65

WARNING: This product can expose you to Silica Dust which is known to the State of California to cause cancer.
For more information, go to www.P65Warnings.ca.gov.

California Proposition 65 – CRT: Listed Date/Carcinogenic substance
Crystalline Silica (CAS 14808-60-7)

Listed: October 1, 1988

SDS Revised: September 2018

END OF SDS

Warranty: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. PROLINE Dura-Corp accepts no responsibility and disclaims all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.